



35W-4200LM
45W-5400LM
55W-6600LM

Features:

1. Up to 120 lm/watt
2. Modern, stylish, excellent surface treatment
3. Water proof, Dust proof, Corrosion proof
4. Super-fast installation, suspended or surface mounted
5. Low operating temperature, makes it extremely versatile under different easy/hard operating conditions
6. Light weight
7. 5 Years Guarantee



TRIPO Series LED TRIPROOF LIGHTS

SHEENLY®

Overview

TRIPO Series LED triproof lights are using SMD2835, providing excellent lumen output, long-lasting stability and splendid sight. Provide 5 years warranty on luminaire.



Color Optional

Black, Silver or other RAL colors available on request.

LED LUMINOUS SOURCE




SMD2835 Illumination grade LED light source.

Luminaire Body


Use high-quality PC+ABS material, high light transmittance, high efficiency and energy saving.

Average beam angle(50%): 120°



Beam Angle: 120°

Application: Parking lot | Warehouse | Tunnel | Basement | Industrial Lighting



Steel Cables, Screws, and accessories;
CCT Switchable is optional

***Ensure the main electrical supply is
switched off before adjusting CCT**



Pendant/Surface Mounted

TRIPO Series LED TRIPROOF LIGHTS

SHEENLY®

Features	Data			
Norminal Wattage	35W	45W	45W	55W
Dimension (mm)	1230*77*66	1230*77*66	1530*77*66	1530*77*66
Weights	1.35kg	1.35kg	1.65kg	1.65kg
Input Voltage AC	220-240 V/AC			
LED Brand	SMD2835			
Fuction	on/off			
Driver Brand	Sheenly Driver			
Operating Temperature	-20 to +40°C			
Power Factor(PF)	>0.95			
THD	THD <20%			
Lumen Output(+/-5%)	4200	5400	5400	6600
Luminarie efficiency(+/-5%)	120 lm/W			
Beam Angle	120°			
Ra	Ra>80			
CCT	3000K/ 4000K/ 5000K/ 5700K			
Rating	IP65 IK09			
Material	PC + ABS			
Installation	Bracket installation/ Hanging ring installation/ Hanging rod installation			
Accessories(Optional)	Motion Sensor/ Emergency Kits for Optional			
Shell Color	Black/ White/ Silver/ Others Upon Request			
Lumen Maintenance	>50000H L70/B50 at 25°C			
Certifications	UL DLC CE ROHS ISO9001 TM21			
Packaging Type	Packaging Data			

DIMENSION DATA



Power	Dimension A (mm)	Dimension B (mm)	Dimension C (mm)
35W	1230	77	66
45W	1230	77	66
45W	1530	77	66
55W	1530	77	66

ORDERING INFORMATION

Part Number	Power	CCT	Lumen Output	Beam	Dimension
SL-TRL-35W-XW-A4	35W	3000K/4000K/5000K/5700K	4200 lm	120°	1230*77*66 mm
SL-TRL-45W-XW-A4	45W	3000K/4000K/5000K/5700K	5400 lm	120°	1230*77*66 mm
SL-TRL-45W-XW-A5	45W	3000K/4000K/5000K/5700K	5400 lm	120°	1530*77*66 mm
SL-TRL-55W-XW-A5	55W	3000K/4000K/5000K/5700K	6600 lm	120°	1530*77*66 mm

PACKAGING DATA

Part Number	Master Carton Size[mm]	Pcs./Inner Box	Pcs./Master Carton	Pcs./20' Container	Pcs./40' Container
SL-TRL-35W-XW-A4	L1300*W225*H290	1	9	2520	5040
SL-TRL-45W-XW-A4	L1300*W225*H290	1	9	2520	5040
SL-TRL-45W-XW-A5	L1600*W225*H290	1	9	2142	4410
SL-TRL-55W-XW-A5	L1600*W225*H290	1	9	2142	4410

Application

Parking lot
Warehouse
Tunnel
Basement
Industrial Lighting



Sheenly Lighting Co., Ltd.

ADD: Bldg 22, Xuhui International, No.1688 Lianhang Road, Shanghai 201112, China
Tel: +86-21-6411-3138 Fax: +86-21-6411-3862
sales@sheenly.com