

Xline CE Version



Features

- High lighting efficiency, up to 100lm/W
- Powerful light output, up to 1500 lm/Meter
- Built-In Driver
- UGR<19, ideal light distribution for Office Lighting
- Super fast installation, suspended or surface mounted
- Connectable. Fast installation, suspended or surface mounted
- Modern, stylish, excellent surface treatment
- Durable with life span over 50,000 hours
- 5 Years Guarantee

Applications

A perfect luminaire for open space area in various applications such as:

- Offices
- Warehouses
- Workshops
- Shops
- Schools
- Supermarkets
- Meeting Rooms



REV 1.2

11/10/2016

Sheenly LED Linear Light

Sheenly's new LED Linear Light Xline is a unique and innovative product, which is the first edge lit linear panel with built-in driver. A hybrid of edge lit technology, with its extremely high efficiency and well controlled UGR, Xline is suitable to be used as a linear high-bay for work place and offices.

Specifications

Dimension (inches[mm])

26W & 40W	45.3"x2.2"x2.6"[1150*55*65]
30W & 50W	57.1"x2.2"x2.6"[1450*55*65]

Power & Lumen Output

26W	2600 lm @ 4000K
30W	3000 lm @ 4000K
40W	4000 lm @ 4000K
50W	5000 lm @ 4000K

Color Temperature

Warm White	3000 ±200K
Natural White	4000 ±250K
Pure White	5700 ±350K

Color Rendering Index >80

Rated Life (L70) 50,000 Hours

Housing Aluminum

Beam Spread 90°

Operating Temperature -20°C to +60°C (Amb.)

Input Voltage 100-277V/AC

Power Factor >0.95

Net Weight 2.0 Kg


Glow Wire 650 °C (850°C Optional)

IP IP40


IK IK05

Installation Suspension
surface mounted

Dimension and Illumination Diagram



	Dimension A (inches [mm])	Dimension B (inches [mm])	Dimension C (inches [mm])
26W & 40W	45.3[1150]	2.6[65]	2.2[55]
30W & 50W	57.1[1450]	2.6[65]	2.2[55]



Ordering Information


Sheenly	Class	Watt	CCT	Finishing	Model
SL=Sheenly Lighting	XLN=Xline	26W 30W 40W 50W	WW=3000 ±200K NW=4000 ±250K PW=5700 ±350K	SI=Silver	N2

Part Number	Power	CCT	Lumen Output	Beam	Dimension (inches[mm])
SL- XLN -26W- WW- N2	26W	3000K ±200K	2300	90°	45.3"x2.2"x2.6"[1150*55*65]
SL- XLN -26W- NW- N2		4000K ±250K	2600	90°	
SL- XLN -26W- PW- N2		5700K ±350K	2600	90°	
SL- XLN -40W- WW- N2	40W	3000K ±200K	3800	90°	
SL- XLN -40W- NW- N2		4000K ±250K	4000	90°	
SL- XLN -40W- PW- N2		5700K ±350K	4000	90°	
SL- XLN -30W- WW- N2	30W	3000K ±200K	2800	90°	57.1"x2.2"x2.6"[1450*55*65]
SL- XLN -30W- NW- N2		4000K ±250K	3000	90°	
SL- XLN -30W- PW- N2		5700K ±350K	3000	90°	
SL- XLN -50W- WW- N2	50W	3000K ±200K	4800	90°	
SL- XLN -50W- NW- N2		4000K ±250K	5000	90°	
SL- XLN -50W- PW- N2		5700K ±350K	5000	90°	

Accessory



Suspension Kit:
Steel Cables, Screws, accessories, etc.



Shanghai Sheenly Lighting Co., Ltd.

No. 2755 SanLu Road, Minhang District Shanghai 201112, China

Tel: (+86)-21-6411 3138 Fax: (+86)-21-6411 3862

*All specifications subject to change without notice.

©2009-2016 Sheenly Lighting all rights reserved.

Available Type: Xline

Patten

